

K•TECH  
*for kitchens*<sup>®</sup>

installation and  
technical  
reference guide

# K-Tech for Kitchens Sheet Flooring

## Technical Data

PATTERN NUMBER	PATTERN NAME	REVERSE SHEETS	RECOMMENDED*		ACTUAL	
			DESIGN MATCH	CROSS DIR. MATCH	DESIGN MATCH	CROSS DIR. MATCH
KT001 – KT009	Transition	No	18"	18"	18"	18"
KT010 – KT012	Beginnings	No	27"	72"	54"	72"
KT030 – KT035	Indulgence	No	27"	36"	27"	36"
KT040 – KT042	Retreat	No	27"	18"	54"	72"
KT050 – KT054	Gatherings	No	18"	12"	54"	144"
KT060 – KT063	Connections	No	18"	36"	54"	36"
KT070 – KT074	Expectations	No	27"	26.18"	54"	144"
KT081 – KT082	Sanctuary	No	18"	18"	54"	72"
KT100 – KT104	Fascination	No	18"	36"	54"	108"

\* K-Tech for Kitchens' recommended design matches offer a more random appearance of natural patterns for an improved installed visual and eliminates waste.

## Product Characteristics

PRODUCT	CONSTRUCTION	PACKAGING		SHIPPING WEIGHT		APPLICABLE FEDERAL SPECIFICATIONS	WARRANTY
		WIDTH	S/Y	PER UNIT	PER PACKAGE		
<b>K-Tech for Kitchens™</b>	Wearlayer: Vinyl Resin and Urethane containing Aluminum Oxide, Fluorinated Polymer and Glass Encapsulated Silver Particles for Antimicrobial Product Protection Cushion: High Density Vinyl Foam Backing: White Shield Filled Fibrous Comp. BAC STOP Protection	12'	80-190	2.8 lbs. Per S/Y	431.5 lbs. Avg.	ASTM F1303 Type I, Grade 2, Class A backing	15 Years

## Fully Adhere or Perimeter Fasten

**K-Tech for Kitchens** provides options for installing the flooring either fully adhered or perimeter fastened over approved wood subfloors, concrete, and properly prepared existing resilient flooring products. The fully adhered method is recommended in complicated room layouts and where the subfloor is in sound condition. Perimeter fastening offers quick and easier installations while cutting down costs, and masking subfloor irregularities.

## K-Tech for Kitchens Adhesive and Seam Sealer

	3044 Premium Flooring Adhesive	SU106 Seam Sealer Kit
<b>Acceptable Subfloors</b>	Dry concrete on all grade levels, suspended wood floors, terrazzo, ceramic, marble, approved resilient floor covering and suitable portland-cement based embossing leveler.	N/A
<b>Proper Trowel Size</b>	1/16" wide x 1/32" deep x 1/32" apart, all substrates	N/A
<b>Working Time</b>	15 – 20 minutes	—
<b>Set Up Time</b>	—	16 hours
<b>Coverage</b>	Fully Adhered: 150 – 270 sq.ft./gallon Perimeter: 4 in. band- 750 lin. ft./gallon Perimeter: 6 in. band- 500 lin. ft./gallon Seams: 8 in. band- 375 lin. ft./gallon	70 lin. ft./kit
<b>Freeze/Thaw Stable</b>	Yes	Not affected by freezing
<b>Flammability</b>	Nonflammable	Flammable liquids
<b>Cleanup</b>	Wet: Soap and water Dry: Clean cloth dampened with mineral spirits.	Wet: Blot with cloth dampened with mineral spirits. Dry: Not removable
<b>Shelf Life</b>	One year if unopened	One year if unopened
<b>Sizes</b>	Qt. (12/carton); 1 gallon (4/carton); 4 gallon	2 fl. oz. per kit (6 kits per carton)

3044 Adhesive – Warning: Eye and skin irritant. SU106 – Warning: Vapor harmful; eye and skin irritant.

## ***Installation Materials***

### **K-Tech for Kitchens Installation and Seaming Video**

5-Pack - English/French/Spanish

Order Code: K10190206S

### **K-Tech for Kitchens Installation Manual**

Order Code: K10170808S (English/Spanish)

Order by phone toll free at 1-888-KTECHINFO.

For more information, visit our website at  
[www.ktechforkitchens.com](http://www.ktechforkitchens.com).

